

- ▶ 适用于操作温度达到450°C
- ▶ 对于玻璃烧瓶，圆形底部最大 20 l.
- ▶ 柔性玻璃丝加热元件
- ▶ 塑料涂层金属外壳
- ▶ 隔热接地
- ▶ 后部的预钻孔螺纹孔允许连接卡箍KM-SK (配件)

BOECO LabHEAT[®] KM-M SERIES

带加热区开关的1.5米电源（接地）电缆



容量 ml/l	烧瓶 \varnothing W	功率	加热 区域	订单号. mm 220V AC	订单号. 110V AC
50	51	55	1	BOE 91000050	BOE 91500050
100	64	100	1	BOE 91000100	BOE 91500100
250	85	150	2	BOE 91000250	BOE 91500250
500	105	200	2	BOE 91000500	BOE 91500500
1	131	300	2	BOE 91001000	BOE 91501000
2	166	500	2	BOE 91002000	BOE 91502000
3	185	600	2	BOE 91003000	BOE 91503000
4	207	750	2	BOE 91004000	BOE 91504000
5	223	860	2	BOE 91005000	BOE 91505000
6	236	1000	2	BOE 91006000	BOE 91506000
10	279	1400	2	BOE 91010000	BOE 91510000
20	345	2000	2	BOE 91020000	BOE 91520000