

試管、平面振盪器

Tube Mixer / Vortex Mixer / Rotator



VM-100-B

VM-100-O

迷你試管振盪器 Mini.Vortex Mixer

- 適用於單支試管混合。
- 速度可調整，按壓直接啟動運轉。
- 頭部由矽膠製成，耐用不易破損。
- For only 1 tube operation.
- Manually press the tube seat to start mixing. The speed is adjustable.
- The upper is made of the silicone, durable and unbreakable.



VM-2000

VM-2000C

試管/平面振盪器 Tube Mixer/Vortex Mixer

- 適用於燒杯、燒瓶或多支試管使用。
- 速度可調整，三段開關。
- 可選擇連續運轉或按壓直接啟動運轉。
- For a beaker, flask or several tubes operation.
- The speed is adjustable through a 3-stage switch.
- Available to select an automatically continuous operation or manually pressing the tube seat to start operation.

Model	VM-100-B	VM-100-O	VM-2000	VM-2000C
轉速 Speed	3,200rpm		3,000rpm	
平台尺寸 Platform Size	Cup Ø21mm		Ø80mm	Cup Ø26mm
外觀尺寸 Overall Size	W55 x D113 x H81mm		W140 x 180 x 180mm	
電源 Power	AC110/220V, 50/60Hz		AC110/220V, 50/60Hz	

平面振盪器 Rotator

- 本機廣泛應用於VDRL、RPR、EIA試驗。
- 速度可調整，可選擇連續運轉或設定運轉。
- 可顯示速度及剩餘時間。
- The machine is widely used in the VDRL,RPR, EIA test.
- Adjustable speed and optional continuous operation or set operation.
- With the display of the speed and remaining time.



DSR-2100D-N



DSR-2800D-N

Model	DSR-2100D-N	DSR-2800D-N
轉速 Speed	20 ~ 240rpm	
計時器 Timer	99min : 59sec	
平台尺寸 Plate size	230 x 230mm	280 x 280mm
旋轉直徑 Rotating diameter	20mm	
載重 Load capacity	20~150 rpm : 2kgs : 150~240 rpm : 1kgs	
電源 Power	AC110/220V, 50/60Hz	