

微量型離心機 Microcentrifuge



MCD-250

特點：

- 採用無刷馬達。
- LCD數位面板，具轉速、離心力之雙重切換、設定及顯示功能。
- 10組記憶系統，可預先設定常用參數。
- 不平衡斷電、過載、故障指示安全防護裝置。

Feature :

- Brushless Motor
- LCD digital panel with RPM & RCF switch, setting & display functions
- 10 memory programs for pre-setting parameters
- With auto power-off safety devices included rotor imbalance, overload, and error indication

Model	MCD-250
轉速 Speed (rpm)	1,000~14,000
最大離心力 Max. RCF (xg)	17,750
最大容量 Max. Capacity (ml)	1.5/2.0 x 24
定時器 Timer (min:sec)	99:59
重量 Weight (kg)	15
尺寸 Size (W x L x H mm)	290 x 420 x 280
電源 Power	AC 110V / 220V, 50/60Hz

◎ 離心試管另購。 Tubes not included.

■ Rotor sets for MCD-250



REA-1518A



REAC-1524



REAC-0232

Rotor	Capacity (ml x pcs)	Tube Size (Ø x L) mm	Max. Speed (rpm)	Max. RCF (xg)
REA-1518A	1.5/2.0ml x 18	9.5~11 x 36~42	14,000	15,780
	0.5ml x 18	7~7.9 x 25~34		
	0.4ml x 18	5.4~6.1 x 26~48		
	0.2ml PCR x 18	5.9~6.3 x 20~24		
REAC-1524	1.5/2.0ml x 24	9.5~11 x 36~42	14,000	17,750
	0.5ml x 24	7~7.9 x 25~34		
	0.4ml x 24	5.4~6.1 x 26~48		
	0.2ml PCR x 24	5.9~6.3 x 20~24		
REAC-0232	0.2ml PCR x 32	5.9~6.3 x 20~24	14,000	15,120